

Cyklop CMT 250 / CHT 400

For medium-weight and heavy packages



Cyklop CMT 250 / CHT 400

A new generation of battery-driven strapping hand tool with display for pre-selection.

Simple, fast and light

- Fully automatic and semi-automatic mode with pushbutton for tensioning, welding and cutting off the strap
- Simple to adjust with 3 modes of operation depending on type and size of the product
- Up to 4.000 Newton (CHT 400) and 2.500 Newton (CMT 250) tension force for PET strap*
- Soft Mode to 1.600 Newton (CHT 400) and 1.500 Newton (CMT 250) tension force for PP strap*
- Unlimited mobility
- Light weight means comfortable operation

Environmentally friendly and innovative

- Newest environmentally friendly battery technology
- Long life Li-Ion battery without memory
- High amount of strapping cycles per battery charge*

	Cyklop CMT 250	Cyklop CHT 400
Technical Data	Weight: 3,9 kg (incl. Akku) Dimensions (LxWxH): 334 x 138 x 148 mm Tension force: (0) 900 - 2.500 N Soft: (0) 400 - 1.500 N Tension speed: 220 mm/s Friction weld seal Insertion: Strap on strap	Weight: 4,2 kg (incl. Akku) Dimensions (LxWxH): 334 x 138 x 148 mm Tension force: (0) 1200 - 4.000 N Soft: (0) 400 - 1.600 N Tension speed: 175 mm/s Friction weld seal Insertion: Strap on strap
Strapping Material	Type: PET and PP Width: 12-16 mm Thickness: 0,5-1,12 mm	Type: PET and PP Width: 16-19 mm Thickness: 0,8-1,3 mm
Technical Data: Battery	Li-Ion-Battery (Bosch): 14,4 V / 2.6 Ah Charging time: approx. 15-30 min** No. of cycles per battery: 400* Charger voltage: 100, 110, 230 V	Li-Ion-Battery (Bosch): 18 V / 2.6 Ah Charging time: approx. 15-30 min** No. of cycles per battery: 150-350* Charger voltage: 100, 110, 230 V

Options

- Steel plate to protect the surface against wear
- Suspension bow
- Touch panel protection
- Mains connector

*depending on strap, package and strap tension

** after 20 min approx. 70% charging capacity

Subject to Modification.

© Copyright 2009 by Cyklop GmbH

Protectory notice pursuant to ISO 16016 to be observed

Cyklop GmbH, Postbox 50 12 20,
50972 Köln, Germany
Industriestraße 133, Rodenkirchen,
50996 Köln, Germany

Phone: ++49(0)2236/602 0,
Fax Sales: ++49(0)2236/602 228
www.cyklop.com,
info@cyklop.com

CYKLOP
INTERNATIONAL

THE
STRAPPING
COMPANY

Update 11.2009