

Strapping Band

PET Strapping Band



What counts is holding power!

In securing loads, strap tension is not the only aspect involved – holding power is crucial. Cyklop plastic straps offer the crucial advantage of high elasticity and thus ensure optimum holding power and real load securement. Cyklop is one of the leading manufacturers of plastic straps, offering a whole host of innovative products: From the low-cost hand tool for a few packaging procedures per day to fully automated machines and systems for high volumes of loads.

Strap Type	Width mm	Thickness mm	Length meter / roll	Breaking strength N	Finished type	Dia. inside mm	Dia. outside mm
2220	9.2	0.60	3000	2,000	Emboss	406	600
2227	12.0	0.60	2500	2,700	Emboss	406	600
2242	15.5	0.68	1750	4,200	Emboss	406	600
1258	15.5	0.70	1750	5,200	Emboss	406	600
2254	15.5	0.85	1300	5,400	Emboss	406	600
2040	15.5	0.85	1212	5,400	Smooth	406	600
2275	18.5	1.00	950	7,500	Emboss	406	600
HD160090S*	16.0	0.90	3300	6,300	Smooth	406	730
HD190127S**	19.0	1.27	750	10,500	Smooth	406	600

* Jumbo roll ** Jumbo roll available on request

High Tensile Steel Strapping Band



Sometimes simply better.

Steel strapping is the classic method of securing loads – and despite the numerous advantages of plastic strap it is sometimes the better solution, even today. Cyklop supplies steel straps in widths from 16 to 32 mm, plus a comprehensive range of strapping devices: From the simple manual tensioning tool to the convenient automatic strapping machine nothing is left to be desired in terms of customers requirements.

Strap width mm	inch	Thickness mm	Length meter / Kg	Breaking strength N	Weight Kg	Dia. inside mm	Dia. outside mm	Coil winding
16	5/8	0.50	15.9	8,100	43 - 49	406	-/+ 600	Mill
19	3/4	0.50	13.2	9,600	43 - 49	406	-/+ 600	Mill
		0.60	11.5	11,000	43 - 49	406	-/+ 600	Mill
		0.80	8.5	14,500	43 - 49	406	-/+ 600	Mill
32	1-1/4	0.80	5.1	24,200	43 - 49	406	-/+ 600	Ribbon

* Finishes: green painted and waxed, zinc coated and waxed